TDC Rig 8

Brief Specifications

Model	2011 Irontech 242 Freestanding Single Telescoping
Type	Carrier Mounted
Drilling Method	Rotary with air/foam or mud circulation system.
Service Application	Completion and Workover, conventional O&G and CSG. Plug and Abandon, cavitation.
Mast	Freestanding Static Pull Cap 160,000lbs.
	Telescoping 79 ft 4 sheave crown API 4F inspection.
	Range 3 Drill Pipe and tubing
Power Swivel	Venturetech XK90 5,000 ft/lbs Torque. Max static load 90 tons
	3.5" IF connection
Draw works	475 HP 42 x 10 chain driven API 7k & 7F certification, 242Klb rating
Mud System	Trailer mounted 150 bbl Mud Pump and Tank. 250 to 400+ bbl available
BOP	7 -1/16, 5K or 11" 3K Annular and Double Gate Rams packages available. Custom designed BOP trailer with hydraulic loading system from trailer to wellhead
Accum	Integral to Trailer unit and free standing. Remote panel.
Drill Pipe/collars	All subs, collars and stabilizers as required
Pipe Handler	TDC Pty Hydraulic Pipe handler c/w integral catwalk and pipe racks
Auxillarily Equip.	Stripper, elevators and tongs for rods Farr tubing tongs. 3k or 5k psi Choke manifold Self-Contained camps c/w Rec room and sep Gymnasiums. Water tankers, bulk fuel tankers, drill tools and hammers, flare tanks, blooie lines, Site accommodation. Case model 821B forklift/ loader and float