# TDC CTU Rig 12

## Brief Specifications

| | |
|---|---|
| **Model** | Axon DCT 800 VTL |
| | Detroit Diesel 310 Hp Turbo Diesel |
| **Type** | Trailer Mounted Self Deploying Injector, onboard pump |
| **Drilling Method** | Steerable Downhole Motor fluid type. |
| **Application** | Well Intervention vertical and horizontal, drilling/milling, wellbore clean outs, plug & abandon, fishing, convey E-line and ESP. Pipeline cleanout. |
| **Injector** | Stewart & Stevenson 800 Series<br>Mast mounted Injector<br>Inj Head lift 72" Ground Clearance 4.1m<br>Tilt angle 35 to 90 deg,<br>Static Pull Cap 80,000 lbs.<br>Max thrust 40,000 lbs. |
| **Reel Capacity** | 1.00" O.D CT x 4,000m<br>2.875" O.D CT x 1,200m<br>2.625" O.D CT x 1,500m<br>2.375" O.D CT x 1,900m (in stock)<br>2.00" O.D CT x 1,450m (in stock) |
| **Mud Pump** | 1 x Triplex 3 plunger SC300 Pumps, 400 HP. 2500 psi |
| **Lubricators** | 1.2m, 2.2m, 3.25m c/with 7 1/16" 5K flanges |
| **Gooseneck** | 72" Radius |
| **BOP** | 5k Tandem Ram BOPs |

| | |
|---|---|
| **Accum** | Nitrogen Back up c/w remote panel. |
| **CT Stripper** | MWP 10,000psi, 7 1/16" 3K Flange x 5K flange |
| **CT connectors** | Clamps and double roll on connectors, external dimple connectors and Grapple/collect type available. |
| **Auxillarily Equip.** | Air Drill Packages 2700 CFM at 1450 psi.<br>Mud Pumps and tanks<br>Downhole motors<br>Fishing tools<br>A Frame Sub Base for increased air gap or raised wellhead available.<br>Self-Contained camps c/w Rec room and sep Gymnasiums.<br>Water tankers, bulk fuel tankers, drill tools and hammers, flare tanks, blooie lines, Site accommodation. |

*All clients equipment needs can be met, please contact our office to arrange a quote.